

STEELS



www.rimconn.com



Commercial Steel Wheels

Discover unmatchable product, service, and a commitment to keeping you on the road safe and smooth.





Truck Wheels



Bus Wheels



Light Truck Wheels



Trailer Wheels

European Vehicles

		Offset / Inset (ET)	Center Hole Dia	PCD	Number of Stud	Bolt Hole Dia.	Load Capacity		
Rimconn PN	Wheel Size	(mm)	(mm)	(mm)	Holes	(mm)	(kg)		
15° HUB PILOTED TUBELESS STEEL WHEELS									
RCST03055		125	161	205	6	21	2000		
RCST03056		131	161	205	6	21	1850		
RCST03060	17.5x6.00	125	202	245	6	21	1850		
RCST03062		134	202	245	6	21	1850		
RCST03063		0 ET	161	205	6	21	2725		
RCST03069		135	191	245	6	23	2		
RCST03071		139	202	245	6	21	2360		
RCST03072		140	221	275	8	24	2360		
RCST03075	17.5x6.75	145	221	275	8	24	2360		
RCST03079		55 ET	176	225	10	26	3000		
RCST03081		135	176	225	10	26	3000		
RCST03088		145	221	275	8	24	2500		
RCST03090		151	221	275	8	26	3000		
RCST03092	19.5x7.50	155	221	275	8	24	3000		
RCST03099		170	221	275	8	24	3150		
RCST03102	19.5x8.25	66 ET	176	225	10	26	3750		
RCST03106		66 ET	221	275	8	26	3750		
RCST03110	19.5x11.75	120 ET	281	335	10	26	4500		
RCST03112		0 ET	221	275	8	24	5150		
RCST03114		120 ET	221	275	8	26	5150		
RCST03115	19.5x14.00	0 ET	281	335	10	26	5150		
RCST03116		120 ET	281	335	10	26	5000		
RCST03118		160	221	275	8	24	3250		
RCST03119		153	281	335	10	26	3750		
RCST03120	00 5.7 50	156	281	335	10	26	4000		
RCST03121	22.5x7.50	160	281	335	10	26	3750		
RCST03125		165	281	335	10	26	4100		
RCST03128		88 ET	281	335	10	26	3550		
RCST03129		163	281	335	10	26	4000		
RCST03132	00 5 0 05	165	281	335	10	26	4000		
RCST03134	22.5x8.25	170	281	335	10	26	4000		
RCST03136		55 ET	281	335	10	26	3650		
RCST03139		115 ET	281	335	10	26	4500		
RCST03141		120 ET	281	335	10	26	4250		
RCST03147	22.5x9.00	175	281	335	10	26	4250		
RCST03150		175	281	335	10	26	5000		
RCST03153		0 ET	281	335	10	26	4000		
RCST03157		120 ET	281	335	10	26	5000		
RCST03158		120 ET	281	335	10	26	6000		
RCST03160	22 5::44 75	135 ET	281	335	10	26	5000		
RCST03163	22.5x11.75	0 ET	221	275	8	24	4500		
RCST03165		0 ET	281	335	10	26	5000		
RCST03170		45 ET	281	335	10	26	5000		
RCST03177		0 ET	281	335	10	26	6000		
RCST03178	22.5x13.00	72 ET	281	335	10	26	6000		
RCST03179		120 ET	281	335	10	26	6000		
RCST03181		0 ET	281	335	10	26	6000		
RCST03183	22 5244 00	70 ET	281	335	10	26	6000		
RCST03184	22.5x14.00	103 ET	281	335	10	26	6000		
RCST03185		155 ET	281	335	10	26	6000		
RCST03187		(-) 63 ET	281	335	10	26	5300		
RCST03189	22 545 00	0 ET	281	335	10	26	5300		
RCST03190	22.5x15.00	25 ET	281	335	10	26	5300		
RCST03191		120 ET	281	335	10	26	5300		
RCST03205	0.504	180	281	335	10	26	6000		
RCST03206	8.5x24	185	281	335	10	26	5000		
ı	ı	1	1	I	I	I	ı		

European Vehicles

European vernoies									
Rimconn PN	Wheel Size	Offset / Inset (ET) (mm)	Center Hole Dia (mm)	PCD (mm)	Number of Stud Holes	Bolt Hole Dia. (mm)	Load Capacity (kg)		
15° STUD PILOTED TUBELESS STEEL WHEELS									
RCST03052		115	146	203.2	5	32.5/37.5	1750		
RCST03053		120	150	208	5	32.5/37.5	1850		
RCST03054		125	161	205	6	21.5/27	1550		
RCST03061	17.5x6.00	125	202	245	6	21.5/27	1850		
RCST03064		0 ET	161	205	6	21.5/27	2725		
RCST03065		124	176	225	10	27/32	3000		
RCST03066		133	176	225	10	27/32	3000		
RCST03068		138	161	205	6	21.5/27	2360		
RCST03070		139	202	245	6	21.5/27	2360		
RCST03073		140	221	275	8	27/32	3000		
RCST03076		0 ET	161	205	6	21.5/27	3000		
RCST03078	47.5.0.75	0 ET	176	225	10	27/32	3000		
RCST03080	17.5x6.75	55 ET	176	225	10	27/32	3000		
RCST03082		135	176	225	10	27/32	3000		
RCST03083		140	176	225	10	27/32	3000		
RCST03084		145	176	225	10	27/32	3000		
RCST03087		145	221	275	8	27/32	2500		
RCST03091		155	221	275	8	27/32	3000		
RCST03089		151	221	275	8	27/32	3000		
RCST03093		0 ET	161	205	6	21.5/27	2725		
RCST03094	19.5x7.50	151	176	225	10	27/32	2725		
RCST03095		0 ET	221	275	8	27/32	2725		
RCST03096		151	221	275	8	27/32	3000		
RCST03098		170	221	275	8	27/32	3350		
RCST03100		0 ET	161	205	6	21.5/27	3350		
RCST03101		0 ET	176	225	10	27/32	3350		
RCST03104		0 ET	221	275	8	27/32	3350		
RCST03103	19.5x8.25	160	176	225	10	27/32	3350		
RCST03108	-	160	221	275	8	27/32	3350		
RCST03105		35 ET	221	275	8	27/32	3350		
RCST03107		152	221	275	8	27/32	3000		
RCST03109	19.5x11.75	0 ET	221	275	8	27/32	4500		
RCST03111	19.5x14.00	0 ET	221	275	8	27/32	5150		
RCST03122		160	281	335	10	27/32	3350		
RCST03126	22.5x7.50	165	281	335	10	27/32	3750		
RCST03127	22.007.00	0 ET	221	275	8	27/32	3150		
RCST03135		0 ET	281	335	10	27/32	3550		
RCST03130	22.5x8.25	163	281	335	10	27/32	3750		
RCST03137		175	221	285	8	32.5/37.5	4000		
RCST03142		167	281	335	10	32.5/37.5	4000		
RCST03145	22.5x9.00	175	281	335	10	27/32	5000		
RCST03154		0 ET	281	335	10	27/32	4000		
RCST03167		0 ET	281	335	10	27/32	5000		
RCST03169	22.5x11.75	34 ET	281	335	10	27/32	5000		
RCST03176	22.5x13.00	0 ET	281	335	10	27/32	6000		
RCST03170	22.07.10.00	0 ET	281	335	10	27/32	6000		
RCST03180	22.5x14.00	4 ET	281	335	10	27/32	6000		
RCST03182	22.0X 14.00	167 ET	281	335	10	27/32	5600		
KU3103100	L	107 E1	201	333	10	21/32	3000		





European Vehicles

Europeum vemoies									
Rimconn PN	Wheel Size	Offset / Inset (ET) (mm)	Center Hole Dia (mm)	PCD (mm)	Number of Stud Holes	Bolt Hole Dia. (mm)	Load Capacity (kg)		
5° MULTIPIECE - TUBE / TUBELESS TYPE STEEL WHEELS									
RCST03192	7.0-20	152	281	335	10	26	2500		
RCST03193	7.5-20	165	281	335	10	27/32	3000		
RCST03194	8.0-20	174	281	335	10	27/32	3250		
RCST03195		241 ET	281	335	10	26	3350		
RCST03196		175	281	335	10	26	3750		
RCST03197	8.5-20	175	281	335	10	27/32	3750		
RCST03198	6.5-20	175	281	335	10	26	4500		
RCST03199		174	281	335	10	26	5000		
RCST03200	8.5-24	180	281	335	10	26	4750		
RCST03201	0.5-24	180	281	335	10	26	5000		
RCST03202		180	281	335	10	27/32	5000		
RCST03207		95 ET	161	205	6	21	2750		
RCST03209	11-20SDC	100 ET	221	275	8	24	3150		
RCST03210	11-203DC	119 ET	221	275	8	24	3500		
RCST03208		87 ET	221	275	8	27/32	3550		
RCST03215		161 ET	281	335	10	26	4750		
RCST03217	10.00V-20	214	281	335	10	26	5000		
RCST03214	10.00 v-20	0 ET	281	335	10	27/32	5000		
RCST03216		184 ET	281	335	10	27/32	4250		
RCST03218		118 ET	221	275	8	24	4500		
RCST03222		115 ET	281	335	10	26	6500		
RCST03223		120 ET	281	335	10	26	5600		
RCST03224		120 ET	281	335	10	26	5600		
RCST03225	10.00W-20	121.5 ET	281	335	10	26	6500		
RCST03226		216	281	335	10	26	5000		
RCST03219		103 ET	221,45	285,75	10	32.5/37.5	5000		
RCST03220		113 ET	281	335	10	26/32	5000		
RCST03221		113 ET	281	335	10	26/32	5000		
	TRILEX TYPE STEEL WHEELS & SPACERS								
RCST00253	8,5-20 Trilex			-					
RCST00254	10,00-20 Trilex			-					
RCST00255	8,5-24 Trilex			-					
RCST00256	10,00-24 Trilex			-					
RCSTS0001	20" Spacer Trilex			-					
RCSTS0002	20" Spacer Trilex			-					
RCSTS0003	24" Spacer Trilex	-							
RCSTS0004	24" Spacer Trilex			-					





American Vehicles

Amei	ncan								
		Offset / Inset (ET)	Center Hole Dia	PCD	Number of Stud	Bolt Hole Dia	Load Capacity		
Rimconn PN	Wheel Size	(mm / Inches)	(mm / Inches)	(mm / Inches)	Holes	(mm / Inches)	(kg / Lbs)		
			UB PILOTED T	1	EEL WHEELS				
RCST03015	17.5x6.75	142 / 5.6"	221 / 8.705"	275 / 10.87"	8	26 / 1.02"	2955 / 6500		
RCST03016	17.5x6.75	157 / 6.2"	220 / 8.665"	222.25 / 8.75"	10	26 / 1.02"	2955 / 6500		
RCST03017	19.5x6.75	142 / 5.6"	221 / 8.705"	275 / 10.87"	8	24 / 0.94"	2273 / 6500		
RCST03020	19.5x7.50	163 / 6.4"	220 / 8.665"	285.75 / 11.25"	10	26 / 1.02"	3045 / 6700		
RCST03018	22.5x7.50	165 / 6.5"	221 / 8.705"	275 / 10.87"	8	24 / 0.94"	3005 / 6600		
RCST03021	22.5x7.50	165 / 6.5"	220 / 8.665"	285.75 / 11.25"	10	26 / 1.02"	3227 / 7100		
RCST03022	22.5x7.50	165 / 6.5"	220 / 8.665"	285.75 / 11.25"	10	26 / 1.02"	3227 / 7100		
RCST03019	22.5x8.25	168 / 6.6"	221 / 8.705"	275 / 10.87"	8	24 / 0.94"	3364 / 7400		
RCST03023	22.5x8.25	168 / 6.6"	220 / 8.665"	285.75 / 11.25"	10	26 / 1.02"	3364 / 7400		
RCST03024	22.5x8.25	168 / 6.6"	220 / 8.665"	285.75 / 11.25"	10	26 / 1.02"	3364 / 7400		
RCST03025	22.5x8.25	168 / 6.6"	220 / 8.665"	285.75 / 11.25"	10	26 / 1.02"	3636 / 8000		
RCST03026	22.5x8.25	168 / 6.6"	220 / 8.665"	285.75 / 11.25"	10	26 / 1.02"	3636 / 8000		
RCST03027	22.5x9.00	147 / 5.8"	220 / 8.665"	285.75 / 11.25"	10	26 / 1.02"	4545 / 10000		
RCST03028	22.5x9.00	178 / 7"	220 / 8.665"	285.75 / 11.25"	10	26 / 1.02"	4545 / 10000		
RCST03029	24.5x8.25	168 / 6.6"	220 / 8.665"	285.75 / 11.25"	10	26 / 1.02"	3364 / 7400		
RCST03030	24.5x8.25	168 / 6.6"	220 / 8.665"	285.75 / 11.25"	10	26 / 1.02"	3364 / 7400		
RCST03031	24.5x8.25	168 / 6.6"	220 / 8.665"	285.75 / 11.25"	10	26 / 1.02"	3636 / 8000		
RCST03205	24x8.5	180 / 7.1"	281 / 11.06"	335 / 13.19"	10	26 / 1.02"	6000 / 13200		
RCST03206	24x8.5	185 / 7.3"	281 / 11.06"	335 / 13.19"	10	26 / 1.02"	5000 / 11000		
		15° S	TUD PILOTED 1	UBELESS ST	EEL WHEELS	3			
RCST03057	17.5x6.00	127	164	222.25	6	32.5/37.5	1850 / 4070		
RCST03058	17.5x6.00	136	164	222,25	6	32.5/37.5	1850 / 4070		
RCST03086	19.5x6.75	140	164	222,25	6	32.5/37.5	2180 / 4800		
RCST03032	24.5x8.25	168 / 6.6"	220 / 8.665"	285.75 / 11.25"	10	31.5-37 / 1.24" -1.45"	3364 / 7400		
RCST03033	22.5x12.25	115 / 4.5"	220 / 8.665"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5182 / 11400		
RCST03034	22.5x12.25	134 / 5.3"	220 / 8.665"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5182 / 11400		
RCST03043	22.5x12.25	115 / 4.5"	221.8 / 8.735"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5182 / 11400		
RCST03044	22.5x12.25	134 / 5.3"	221.8 / 8.735"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5182 / 11400		
RCST03035	22.5x13.00	13 / 0.5"	220 / 8.665"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5000 / 11000		
RCST03036	22.5x13.00	79 / 3.1"	220 / 8.665"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5000 / 11000		
RCST03037	22.5x13.00	123 / 4.8"	220 / 8.665"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5318 / 11700		
RCST03038	22.5x13.00	147 / 5.8"	220 / 8.665"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5182 / 11400		
RCST03045	22.5x13.00	13 / 0.5"	221.8 / 8.735"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5000 / 11000		
RCST03046	22.5x13.00	79 / 3.1"	221.8 / 8.735"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5000 / 11000		
RCST03047	22.5x13.00	123 / 4.8"	221.8 / 8.735"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5000 / 11000		
RCST03039	22.5x14.00	51 / 2"	220 / 8.665"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5000 / 11000		
RCST03040	22.5x14.00	51 / 2"	220 / 8.665"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5000 / 11000		
RCST03041	22.5x14.00	51 / 2.0"	220 / 8.665"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5818 / 12800		
RCST03042	22.5x14.00	0 ET / 0"	220 / 8.665"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5591 / 12300		
RCST03048	22.5x14.00	51 / 2"	221.8 / 8.735"	285.75 / 11.25"	10	32.5-37 / 1.28"-1.45"	5000 / 11000		
15° TUBELESS DEMOUNTABLE / DAYTON STEEL WHEELS									
RCST00001	22.5x7.50	108 / 4.3"	-	-	-	-	3500 / 7700		
RCST00003	22.5x7.50	115 / 4.5"	-	-	-	-	3500 / 7700		
RCST00004	22.5x8.25	121 / 4.8"	-	-	-	-	4000 / 8800		
RCST00005	22.5x9.00	127 / 5"	-	-	-	-	4500 / 9900		
RCST00008	24.5x8.25	120.5 / 4.7"	-	-	-	-	4200 / 9240		
				1					









KNOWLEDGE THAT CONNECTS!



www.rimconn.com