



Discover military-grade wheel systems are engineered to withstand the harshest operational environments. Tested to military standards, these wheels ensure structural integrity, long service life, and uncompromising reliability in mission-critical conditions.





Armoured
Personnel Carrier
Wheels



MRAP Wheels



Military Wheels





RCST04056 10.00-20 70 170 225 10 Ø15 4500 kg / 9900 Lbs RCST04057 10.00-20 80 281 335 10 B22-DS36 4500 kg / 9900 Lbs RCST04058 10.00-20 90 281 335 10 M22 4500 kg / 9900 Lbs RCST04059 10.00-20 100 281 335 10 M22 4500 kg / 9900 Lbs RCST04060 10.00-20 121.5 281 335 10 M22 4500 kg / 9900 Lbs RCST04061 11.00-20 65 281 335 10 M22 4500 kg / 9900 Lbs RCST04062 11.00-20 80 221 275 8 M22 4500 kg / 9900 Lbs	Rimconn PN	Wheel Size	Inset (ET) (mm)	Center Hole Dia. (mm)	PCD Dia (mm)	Number of Stud Holes	Stud Hole Dia / Type (mm)	Load Capacity 100 km/h - 62 Mph (kg /Lbs)
RCST04058 10.00-20 90 281 335 10 M22 4500 kg / 9900 Lbs RCST04059 10.00-20 100 281 335 10 M22 4500 kg / 9900 Lbs RCST04060 10.00-20 121.5 281 335 10 M22 4500 kg / 9900 Lbs RCST04061 11.00-20 65 281 335 10 M22 4500 kg / 9900 Lbs	RCST04056	10.00-20	70	170	225	10	Ø15	4500 kg / 9900 Lbs
RCST04059 10.00-20 100 281 335 10 M22 4500 kg / 9900 Lbs RCST04060 10.00-20 121.5 281 335 10 M22 4500 kg / 9900 Lbs RCST04061 11.00-20 65 281 335 10 M22 4500 kg / 9900 Lbs	RCST04057	10.00-20	80	281	335	10	B22-DS36	4500 kg / 9900 Lbs
RCST04060 10.00-20 121.5 281 335 10 M22 4500 kg / 9900 Lbs RCST04061 11.00-20 65 281 335 10 M22 4500 kg / 9900 Lbs	RCST04058	10.00-20	90	281	335	10	M22	4500 kg / 9900 Lbs
RCST04061 11.00-20 65 281 335 10 M22 4500 kg / 9900 Lbs	RCST04059	10.00-20	100	281	335	10	M22	4500 kg / 9900 Lbs
	RCST04060	10.00-20	121.5	281	335	10	M22	4500 kg / 9900 Lbs
RCST04062 11.00-20 80 221 275 8 M22 4500 kg / 9900 Lbs	RCST04061	11.00-20	65	281	335	10	M22	4500 kg / 9900 Lbs
1100101002 1110020 00 221 2	RCST04062	11.00-20	80	221	275	8	M22	4500 kg / 9900 Lbs
RCST04063 11.00-20 90 221 275 10 B22-DS36 4500 kg / 9900 Lbs	RCST04063	11.00-20	90	221	275	10	B22-DS36	4500 kg / 9900 Lbs
RCST04064 11.00-20 120 221 275 8 M20 4500 kg / 9900 Lbs	RCST04064	11.00-20	120	221	275	8	M20	4500 kg / 9900 Lbs

Main Benefits



Run Flat Adaptable



E CTIS Adaptation



Enviromental Manufacturing



Mine Protection



Bullet Proof Tested



NATO standards





www.rimconn.com