



Rimconn

MATERIAL HANDLING

Wheels





Material Handling

Steel Wheels

Discover unmatched product, service, and a commitment to keeping you reach unlimited heights with durable, efficient and user friendly wheel solutions.



Forklift
Wheels



Reach Stacker
Wheels



AWP
Wheels



Call Us
+90 533 248 6908
+971 58 504 2597



Our Location
Meydan Grandstand,
6th floor, Meydan Road
Nad Al Sheba, Dubai - U.A.E.

Material Handling Wheels

MULTI PIECE WHEELS (2/3/4pcs)



Rimconn PN	Wheel Size	Inset (ET) (mm)	Center Hole Dia. (mm)	PCD Dia (mm)	Number of Stud Holes	Stud Hole Dia / Type (mm)
RCST03583	3.00D-8	(-) 4	62	95	4	14/24/90°
RCST03584		(-) 4	63.2	95	4	18.5/24
RCST03585		25	60	100	4	15.3/22/60°
RCST03586		(-) 3	50	101.6	4	14/19/R12
RCST03587		2	86	105	4	12.5/18/R12
RCST03588		(-) 9	62	115	4	15/22/90°
RCST03589		(-) 5	85	130	4	18.5/24
RCST03590		(-) 5	96	130	4	18/25/R14
RCST03591		16	59	100	5	15
RCST03592		21	80	114	5	18.5/24
RCST03593		0	60	114	5	15/19.8/60°
RCST03594		27	80	114	5	18.5/24
RCST03595		26	80.5	114	5	18.5/24/90°
RCST03596		27	80	115	5	18.5/24
RCST03597		4	80	115	5	13/16/90°
RCST03598		(-) 9	80	120	5	16/20/R12
RCST03599		(-) 4	94.5	126.5	5	18.5/24
RCST03600		1	102.5	134	5	17.5/20.8/60°
RCST03601		(-) 6	101	135	5	14/20/R12
RCST03602		(-) 14	101	136	5	14/20/90°
RCST03603		(-) 4	101	140	5	13.5/17/60°
RCST03604		0	88	140	5	22
RCST03605		(-) 4	94	140	5	18.5/24/90°
RCST03606		(-) 1	105	140	5	15.5
RCST03607		0	105	140	5	15
RCST03608		(-) 10	110	140	5	18.5/24/90°
RCST03609		(-) 5	110	141.5	5	18.5/24
RCST03610		(-) 6	110	145	5	18.5/24/90°
RCST03611		(-) 4	110	145	5	18.5/24
RCST03612		(-) 5	110	146	5	18.5/24

Material Handling Wheels						
Rimconn PN	Wheel Size	Inset (ET) (mm)	Center Hole Dia. (mm)	PCD Dia (mm)	Number of Stud Holes	Stud Hole Dia / Type (mm)
RCST03512	4.33R-8	(-) 8	85	115	4	15
RCST03510		(-) 7	60	98	4	14.5/19.5/90°
RCST03511		(-) 5	60	100	4	14/18/60°
RCST03520		(-) 14	102.5	134	5	17.5/20.8/60°
RCST03513		(-) 12	85	115	4	15/23/90°
RCST03514		(-) 5	85	130	4	18.5/24
RCST03515		(-) 5	96	130	4	18.5/24
RCST03516		19	78	115	5	16.5/22/R14
RCST03517		21	80	120	5	16/20/R12
RCST03518		45	84	130	5	15
RCST03519		37	90	130	5	17.5/20.8/60°
RCST03522		(-) 7	101	135	5	14/20/R12
RCST03521		2	99	135	5	13/21/90°
RCST03573		(-) 26	100	140	6	16.5/22/90°
RCST03523		(-) 6	101	136	5	15/23/90°
RCST03524		(-) 8	102	137	5	15/23/90°
RCST03525		38	93	140	5	16.5
RCST03526		30	93	140	5	15
RCST03527		(-) 8	105	140	5	18/22/60°
RCST03528		(-) 21	105	140	5	15/23/90°
RCST03529		(-) 5.5	105	140	5	15.5
RCST03530		(-) 3.5	105	140	5	20/24/R14
RCST03531		(-) 16	110	140	5	18.5/24/90°
RCST03532		(-) 27	110	142	5	17
RCST03533		4.5	110	143	5	18.5/24
RCST03534		11	110	144	5	20/24/R14
RCST03535		(-) 14	110	145	5	15/24/90°
RCST03536		0	110	145	5	18.5/24
RCST03537		1.5	110	145	5	18.5/24/90°
RCST03538		40	110	145	5	18.5/24
RCST03539		40	110	145	5	15
RCST03540		40	110	145	5	19
RCST03541		30	110	145	5	18.5/24
RCST03542		40	110	145	5	17.5/21/60°
RCST03543		(-) 9	110	145	5	16
RCST03544		16	110	145	5	18.5/24
RCST03545		40	112	145	5	17/22.5/R14
RCST03546		19	112	145	5	18.5/22/60°
RCST03547		42	112	145.5	5	18.5/24
RCST03548		39	110	146	5	18.5/24
RCST03549		(-) 49	110	146	5	21.5/27R16
RCST03550		41.5	110	146	5	18.5/24/90°

Material Handling Wheels						
Rimconn PN	Wheel Size	Inset (ET) (mm)	Center Hole Dia. (mm)	PCD Dia (mm)	Number of Stud Holes	Stud Hole Dia / Type (mm)
RCST03639	4.00E-9	0	94	124	6	18.5/24
RCST03623		0	85	130	4	18.5/24
RCST03624		32	80	114	4	13/17/90°
RCST03625		23	80	114.3	4	18.5/24
RCST03626		0	101	135	4	14/20/90°
RCST03627		(-) 5	101.6	139.7	4	13.5/17/60°
RCST03628		0	93	140	4	18.5/24
RCST03629		0	94	140	4	16/22/90°
RCST03630		(-) 20	110	140	4	18.5/24
RCST03631		(-) 5	110	145	4	18.5/24
RCST03632		(-) 30	110	160	4	18.5/24R14
RCST03633		0	110	160	4	18.5/24
RCST03634		45	110	160	4	18.5/24
RCST03635		(-) 30	110.5	160	4	21.5/27/R18
RCST03636		0	120	160	4	16.5
RCST03637		(-) 16	130	160	4	18.5/24
RCST03638		(-) 12	125	164	4	16.5/22/R14
RCST03640		1.5	110	139	6	13.5
RCST03641		10	103	142	6	27/32R18
RCST03642		(-) 6	123.5	156	6	18.5/24
RCST03643		0	133.5	170	6	18.5/24/90°
RCST03644		(-) 30	144	172	6	16/20.5/R14
RCST03645		(-) 16	130	175	6	18.5/24
RCST03646		(-) 15	150	180	6	18.5/24
RCST03647	6.00E-9	(-) 11	85	130	4	18.5/24
RCST03648		(-) 14	102	137	4	15/23/90°
RCST03649		(-) 23	93	140	4	17
RCST03650		(-) 5	94	140	4	18.5/24
RCST03651		(-) 20	110	145	4	15
RCST03652		20	110	145	4	18.5/24
RCST03653		4	110	147	4	18.5/24
RCST03654		(-) 4	126	153	4	15
RCST03655		(-) 69	126	153	4	15/23/90°
RCST03656		(-) 27	127	153	4	15/22/90°
RCST03657		(-) 6	109	160	4	18.5/24
RCST03658		(-) 65	110	160	4	18.5/24R14
RCST03659		30	110	160	4	18.5/24
RCST03660		0	115	160	4	18.5/24R14
RCST03661		(-) 26	94	124	6	18.5/24
RCST03662		(-) 10	101	140	6	18.5/24
RCST03663		38	102	140	6	28/34/90°
RCST03668		(-) 30	133	170	6	18.5/24

Material Handling Wheels

Rimconn PN	Wheel Size	Inset (ET) (mm)	Center Hole Dia. (mm)	PCD Dia (mm)	Number of Stud Holes	Stud Hole Dia / Type (mm)
RCST03671	5.00F-10	38	62	100	4	14/17/R14
RCST03672		(-) 5	85.5	130	4	18.5/24
RCST03704		(-) 6	150	180	6	17.5/20.8/60°
RCST03674		(-) 6	80	114	4	13/17/90°
RCST03675		(-) 12	103	139.7	4	17/24/60°
RCST03673		(-) 6	97.5	140	4	18.5/24
RCST03677		(-) 3	94	140	4	18.5/24
RCST03678		25	96.8	140	4	18.5/24
RCST03679		40	97.5	140	4	18.5/24
RCST03680		(-) 5	105.5	140	4	15
RCST03681		8	110	145	4	18.5/24
RCST03682		(-) 28	124	153	4	17
RCST03683		48	110	160	4	21.5
RCST03684		0	110	160	4	18.5/24
RCST03685		(-) 8	110	160	4	18.5/24/90°
RCST03686		48	110	160	4	18.5/24R14
RCST03687		18	123	160	4	21.8/26.7/R16
RCST03688		(-) 6	127	165	4	17/22/90°
RCST03689		(-) 4	127	166	4	16.5/22/R14
RCST03690		0	137.7	177.8	4	18.5/24R14
RCST03691		(-) 7	150	188	4	21
RCST03692		(-) 35	150	190	4	18.5/24R14
RCST03693		1	110	139	6	13.5
RCST03694		0	100	140	6	21.5/27/60°
RCST03695		(-) 10	101	140	6	18.5/24R14
RCST03676		0	94	140	4	15
RCST03697		3	124	156	6	18/24/90°
RCST03698		(-) 5	127	160	6	20/23/60°
RCST03699		5	135	170	6	21.5/27R16
RCST03700		(-) 6	140	170	6	17.5/20.8/60°
RCST03701		(-) 30	144	172	6	16/20.5/R14
RCST03702		0	130	175	6	18.5/21.5/60°
RCST03703		(-) 16	146.5	180	6	16/19/60°
RCST03696		(-) 17	110	142	6	17
RCST03705		0	150	183	6	18/21.5/60°
RCST03706		(-) 6	130	160	8	16/19/60°
RCST03707		0	110	145	9	18.5/24
RCST03708		60	100	135	11	16
RCST03709		122	100	135	11	16/24/R14
RCST03710		20	124	149	11	13
RCST03711		20	124	149	12	13.5/17/60°

Material Handling Wheels						
Rimconn PN	Wheel Size	Inset (ET) (mm)	Center Hole Dia. (mm)	PCD Dia (mm)	Number of Stud Holes	Stud Hole Dia / Type (mm)
RCST03756	6.50F-10	50	136	170	10	18.5/24
RCST03713		(-) 5	94	140	5	18.5/24
RCST03714		9	110	144	5	18.5/24
RCST03715		(-) 10	110	145	5	18.5/24R14
RCST03716		35	110	145	5	18.5/24
RCST03717		9	110	145	5	18.5/24
RCST03718		(-) 9	110	145	5	21.5/27/90°
RCST03719		9	110	145	5	18.5/24/90°
RCST03720		(-) 20	110	145	5	18.5/24R14
RCST03721		38	110	146	5	18/23/60°
RCST03722		26	110	146	5	18.5/24
RCST03723		40	111	147	5	18.5/24
RCST03724		33	111	148	5	18.5/24
RCST03725		(-) 20	124	153	5	18.5/24
RCST03726		(-) 9	101	160	5	22.2/26.5/R16
RCST03727		53	110	160	5	21.5/27/90°
RCST03728		54	110	160	5	18.5/24R14
RCST03729		(-) 10	110	160	5	18.5/24
RCST03740		(-) 40	123	156	6	17.5/20.8/60°
RCST03734		0	94	124	6	18.5/24
RCST03742		60	130	170	6	19.5
RCST03743		(-) 73	131	170	6	18
RCST03744		10	135	170	6	18.5/24R14
RCST03745		0	135	170	6	21.5/27R16
RCST03746		35	110	145	7	18.5/24
RCST03747		31	110	145	7	18.5/24/90°
RCST03748		19	108	136	8	14.5/17.5/60°
RCST03749		35	110	145	8	18.5/24
RCST03750		66	110	150	8	20/28/90°
RCST03751		2	110	155	8	18.5/24/90°
RCST03752		38	125	165	8	21/28.5/60°
RCST03753		(-) 17	150	180	8	17.5/22/90°
RCST03754		(-) 5	110	145	9	18.5/24
RCST03755		41	93	140	10	18
RCST03741		(-) 56	130	170	6	20/27/R16
RCST03757		35	136.5	170	10	16/24/R14
RCST03758		4	139	170	10	18.5/24
RCST03759		11	140	170	10	18.5/24
RCST03760		7	144	178	10	18.5/24/90°
RCST03761		(-) 55	144	178	10	18.5/24
RCST03762		10	145	178	10	18.5/24
RCST03763		5	110	135	11	16/24/R14

Material Handling Wheels						
Rimconn PN	Wheel Size	Inset (ET) (mm)	Center Hole Dia. (mm)	PCD Dia (mm)	Number of Stud Holes	Stud Hole Dia / Type (mm)
RCST03767	5.00S-12	20	105	140	5	18.5/24
RCST03768		30	110	160	5	16
RCST03769		(-) 12	163	215	5	22/34/90°
RCST03778		100	161	205	6	21.5/27R16
RCST03771		20	117.8	152.4	6	15/20/90°
RCST03772		(-) 58	120	195	6	21.5/27/90°
RCST03787		(-) 6	166	218	6	32.5/37.5/R22.2
RCST03774		45	136	196	6	32.5/37.5/R22.2
RCST03775		0	160	205	6	18.5/24
RCST03776		(-) 27	160	205	6	21.5
RCST03777		0	161	205	6	18.5/24R14
RCST03791		(-) 6	170	220	6	32.5/37.5/R22.2
RCST03779		45	161	205	6	18.5/24R14
RCST03780		(-) 20	161	205	6	18.5/24R14
RCST03781		32	161	205	6	18.5/24R14
RCST03782		30	161	205	6	18.5/24R14
RCST03783		0	161	205	6	21
RCST03784		(-) 59	176	215	6	18.5/24R14
RCST03785		(-) 57	176	216	6	21.5/27/90°
RCST03786		(-) 6	166	218	6	32.5/37.5/R22.2
RCST03793		(-) 6	170	220	6	32/36/60°
RCST03788		(-) 4	166	219	6	32.5/37.5/R22.2
RCST03789		45	160	220	6	27/32R18
RCST03796		0	144	190	8	27/32/80°
RCST03797		(-) 4	145	190	8	19/24/60°
RCST03798		0	144	240	8	18.5/24/90°
RCST03800		13	93	140	10	18
RCST03801		49	110	160	10	21
RCST03802		57	178	210	14	16
RCST03803	8.00G-12	(-) 41	105	140	5	15.5
RCST03804		35	110	160	5	16
RCST03806		40	111	160	5	18.5/24
RCST03808		(-) 51	150	190	5	20/28/90°
RCST03820		(-) 65	161	205	6	19
RCST03811		81	135	170	6	18.5/24R14
RCST03812		(-) 15	140	170	6	18/21/60°
RCST03813		(-) 38	150	180	6	17.5/22/60°
RCST03814		42	136	196	6	32.5/37.5/R22.2
RCST03815		(-) 21	160	201.5	6	18.5/24R14
RCST03816		(-) 8	160	205	6	21/28/90°
RCST03817		34	160	205	6	21.5
RCST03818		(-) 46	160	205	6	20/26/90°

Material Handling Wheels						
Rimconn PN	Wheel Size	Inset (ET) (mm)	Center Hole Dia. (mm)	PCD Dia (mm)	Number of Stud Holes	Stud Hole Dia / Type (mm)
RCST03850	5.5-15	0	160	205	6	21.5
RCST03852		53	168.5	220	6	32.5/37.5/R22.2
RCST03853		110	168.5	220	6	32.5/37.5/R22.2
RCST03855		109.5	202	245	6	26
RCST03856		20	152.4	203.2	8	17.5/23/90°
RCST03857		111	221	275	8	21.5/27R16
RCST03859		104	176	225	10	27/32R18
RCST03854		110	170	220	6	32.5/37.5/R22.2
RCST03849		20	117.8	152.4	6	15/20/90°
RCST03908	6.0-15	40	243	280	9	21.5/27/90°
RCST03862		32	154.4	222.2	6	32.5/37.5/R22.2
RCST03863		114	192	270	6	32.5/37.5/R22.2
RCST03864		15	221	275	6	27/32R18
RCST03865		110	176	225	10	27/32R18
RCST03900		35	221	275	8	26
RCST03901		135	221	275	8	21.5/27R16
RCST03903		123	221	275	8	27/32R18
RCST03905		64	224	275	8	24/33/60°
RCST03906		(-) 27	229	275	8	24
RCST03907		123	245	290	8	24/33/60°
RCST03909		54	164	223	10	32/37/60°
RCST03910		121	176	225	10	27/32R18
RCST03913		93	176	225	10	24
RCST03914		128	230	283	12	27/32R18
RCST03915		38	230	283	12	27/32R18
RCST03916		130	230	285	12	27/32R18
RCST03878	6.5-15	30	161	222.25	6	32.5/37.5/R22.2
RCST03879		(-) 18.5	186	240	6	24
RCST03881		123	194	250	6	32.5/37.5/R22.2
RCST03882		73	200	250	6	32.5/37.5/R22.2
RCST03883		79	200	260	6	32.5/37.5/R22.2
RCST03884		164	200	260	6	32.5/37.5/R22.2
RCST03885		3	209	270	6	29/33/60°
RCST03886		0	221	275	6	32.5/37.5/R22.2
RCST03887		(-) 11	152.4	203.2	8	17.5/23/90°
RCST03888		(-) 37.5	221	260	8	18.5/24R14
RCST03889		(-) 6	190	270	8	27/31.5/60°
RCST03891		124	221	275	8	27/32R18
RCST03892		(-) 76	221	275	8	27/32R18
RCST03866		125	161	205	6	21.5/27R16
RCST03867		168	161	205	6	21
RCST03869		75	161	205	6	18.5/24R14

Material Handling Wheels

Rimconn PN	Wheel Size	Inset (ET) (mm)	Center Hole Dia. (mm)	PCD Dia (mm)	Number of Stud Holes	Stud Hole Dia / Type (mm)
RCST03919	7.0-15	3	160	205	6	20/26/90°
RCST03917		41	136	196	6	32.5/37.5/R22.2
RCST03935		37	164	223	6	32.5/37.5/R22.2
RCST03920		131	161	205	6	20
RCST03922		34	161	205	6	18
RCST03923		(-) 5	161	205	6	18.5/24R14
RCST03924		(-) 36.5	176	216	6	18.5/24R14
RCST03925		(-) 4	170	219	6	32.5/37.5/R22.2
RCST03926		(-) 4	165	220	6	32.5/37.5/R22.2
RCST03927		47.5	168.5	220	6	32.5/37.5/R22.2
RCST03928		(-) 26	170	220	6	27/31.5/60°
RCST03929		201	170	220	6	32.5/37.5/R22.2
RCST03930		47	170	220	6	32.5/37.5/R22.2
RCST03931		(-) 26	170	220	6	32/36/60°
RCST03932		(-) 11	170	220	6	32/38/90°
RCST03933		52	176	220	6	27/32R18
RCST03934		30	161	222.25	6	32.5/37.5/R22.2
RCST03921		(-) 35	161	205	6	21.5/27R16
RCST03936		39.5	125	165	8	21/28.5/60°
RCST03937		21	220	275	8	26
RCST03938		55	221	275	8	27/32R18
RCST03939		0	221	275	8	27/32R18
RCST03940		15	221	275	8	27/32R18
RCST03941		142.5	221	275	8	27/32R18
RCST03942		203	221	275	8	27/32R18
RCST03943		39.5	110	158	10	22/24/90°
RCST03944		(-) 50	144	178	10	18.5/24R14
RCST03945		(-) 73.5	165	220	10	26/32/R18
RCST03947		134	170	225	10	22
RCST03948		0	175	225	10	27/32R18
RCST03949		174	175	225	10	27/32R18
RCST03951		131	176	225	10	26
RCST03952		201	176	225	10	27/32R18
RCST03954		50	176	225	10	24
RCST03955		81	202	245	10	20
RCST03956		67.5	178	210	14	16
RCST03957	7.5-15	41	136	196	6	32.5/37.5/R22.2
RCST03958		40	221	275	6	27/32R18
RCST03959		90	221	275	6	19/25/R14
RCST03960		140	176	225	10	24
RCST03961		81	178	210	14	16

Material Handling Wheels

Rimconn PN	Wheel Size	Inset (ET) (mm)	Center Hole Dia. (mm)	PCD Dia (mm)	Number of Stud Holes	Stud Hole Dia / Type (mm)
RCST03962	8.0-15	(-) 38	161	205	6	20/26/90°
RCST03963		0	161	205	6	27/32R18
RCST03964		70	161	205	6	21
RCST03965		(-) 46	202	245	6	26.5
RCST03966		27	200	250	6	32.5/37.5/R22.2
RCST03967		57.5	200	261	6	32.5/37.5/R22.2
RCST03968		0	190	270	8	27/31.5/60°
RCST03969		161	221	275	8	26
RCST03970		2	221	275	8	18.5/24R14
RCST03971		0	221	275	8	21.5/27/90°
RCST03972		(-) 6	221	275	8	27/32R18
RCST03973		(-) 65	221	275	8	27/32R18
RCST03974		160	221	275	8	27/32R18
RCST03975		33	221	275	8	27
RCST03976		70	224	275	8	24/33/60°
RCST03977		58.5	229	275	8	24
RCST03978		40	221	285	8	26
RCST03979		55	176	225	10	27/32R18
RCST03980		97	202	245	10	20
RCST03981		161	221	275	10	24
RCST03982		95	221	275	10	24
RCST03983		182	221	275	12	26
RCST03984		37.5	221	275	12	26
RCST03985		62	230	283	12	27/32R18
RCST03986	9.75-15	80	161	205	6	21
RCST03987		0	161	205	6	18.5/24R14
RCST03988		(-) 45.5	170	220	6	32.5/37.5/R22.2
RCST03989		(-) 65.5	144	190	8	32.5/37.5/R22.2
RCST03990		54	221	275	8	27/32R18
RCST03991		0	221	275	8	24
RCST03992		0	221	275	8	18.5/24R14
RCST03993		50.8	176	225	10	27/32R18
RCST03994		0	176	225	10	24
RCST03995		45	176	225	10	27/32R18
RCST03996		35	176	225	10	24
RCST03997		(-) 45	260	300	10	24
RCST03998		52.5	178	210	14	16
RCST03999		(-) 16	270	305	16	17.5



SPLIT WHEELS



Rimconn PN	Wheel Size	Inset (ET) (mm)	Center Hole Dia. (mm)	PCD Dia (mm)	Number of Stud Holes	Stud Hole Dia / Type (mm)
RCST04000	2.50C-4	(-) 3	52	68	6	Ø8.5
RCST04001		(-) 3	49	70	6	Ø8.5
RCST04002	3.00D-8	(-) 4	62.5	159	4	16/20/R12
RCST04003		(-) 4	62.5	159	4	Ø15
RCST04004		(-) 4	62.8	155	4	14/18/90°
RCST04005		(-) 4	60	158	4	13.5/17/60°
RCST04006		(-) 4	60	158	4	16/20/R14
RCST04007		(-) 4	50	158	4	Ø11
RCST04008		(-) 4	85	158	4	Ø14.5
RCST04009		(-) 4	85	152	4	18.5/24/R14
RCST04010		(-) 4	85	158	4	18/22/90°
RCST04011		(-) 4	85	155	4	18.5/24/R14
RCST04012		(-) 4	85	155	4	18.5/24/R14
RCST04013		(-) 4	64	155	5	14.5/17/60°
RCST04014		(-) 4	101	150	5	14/20/90°
RCST04015		(-) 4	94	140	5	18.5/24/R14
RCST04016		(-) 4	94	140	5	Ø18.5
RCST04017		(-) 4	94	150	5	Ø18.5
RCST04018		(-) 4	110	145	5	18.5/24/R14
RCST04019		(-) 4	80	158	6	Ø13
RCST04020		(-) 4	80.5	155	6	Ø13
RCST04021		(-) 4	94	155	6	16.5/21/60°
RCST04022		(-) 4	110	155	6	16/19/60°
RCST04023		(-) 4	100	158	6	16/19/60°
RCST04024		(-) 4	110	155	6	15/22/90°
RCST04025		(-) 4	110	158	6	16/19/60°
RCST04026		(-) 4	110	158	6	16/19/60°
RCST04027		(-) 4	110	155	6	14/20/90°
RCST04028		(-) 4	120	162	6	18.5/24/R14

Material Handling Wheels

Rimconn PN	Wheel Size	Inset (ET) (mm)	Center Hole Dia. (mm)	PCD Dia (mm)	Number of Stud Holes	Stud Hole Dia / Type (mm)
RCST04029	4.00E-9	(-) 5	85	175	4	18.5/24/R14
RCST04030		(-) 5	85	175	4	18.5/24/R14
RCST04031		(-) 5	94	175	5	18.5/24/R14
RCST04032		(-) 5	124	167	5	16/19/60°
RCST04033		(-) 5	85	172	6	Ø12
RCST04034		(-) 5	94	172	6	18.5/24/R14
RCST04035		(-) 5	94	175	6	18.5/24/R14
RCST04036		(-) 5	94	175	6	18.5/24/R14
RCST04037		(-) 5	125	175	6	18.5/24/R14
RCST04038		(-) 5	140	170	6	17.5/20.8/60°
RCST04039		(-) 5	120	175	6	18.5/24/R14
RCST04040		(-) 5	150	180	6	17/20.8/60°
RCST04041		(-) 5	130	160	8	16/19/60°
RCST04042	4.00E-10	(-) 3	135	175	5	16/18.5/60°
RCST04043		(-) 3	135	175	5	20/25/90°
RCST04044	3.00D-13	(-) 4	94	275	5	16.5/24/R14
RCST04045		(-) 4	94	290	5	18.5/22/90°
RCST04046		(-) 4	142.5	270	6	Ø21
RCST04047		(-) 4	160	270	6	Ø21
RCST04048	3.75P-13	10	85	275	4	Ø14.5
RCST04049		10	94	275	4	16.5/24/R14
RCST04050		10	132	275	4	16.5/24/R14
RCST04051		10	140	275	6	18.5/24/R14
RCST04052		10	160	275	6	21.5/27/R16
RCST04053		10	160	270	6	Ø21
RCST04054		(-) 20	161	290	6	21.5/27/R16
RCST04055		(-) 20	161	285	6	21.5/27/R16





KNOWLEDGE THAT CONNECTS!



www.rimconn.com